



# Split-Type IP Camera

## 2MP, 3.7mm, 10M IR

### HLC-3CKDS

- 2 Megapixel Split-Type IP Camera
- H.264+/ H.264/ M-JPEG Compression
- Functional and Extremely Discreet Design
- Easy and Flexible Installation
- Digital Wide Dynamic Range
- The sensor unit and main unit are connected by an 3 Meters
- Shutter Speed Adjustable / 2-way Audio
- Digital Noise Reduction / Power over Ethernet
- Support iPhone/ Mac/ Android
- SDK for Software Integration
- Free Bundle 36Ch Recording Software



### Specification

Hardware	
CPU	Multimedia SoC
RAM	512 MB
Flash	32 MB
Image Sensor	1 / 2.9" Megapixel SONY CMOS Sensor
Sensitivity	Color: 0.01 Lux(AGC ON)
Lens	3.7mm @ F2.4
View Angle	75.14°(H), 38.05°(V)
I/O	1 DI / 1 DO
Audio	G.711(64K) and G.726(32K, 24K) audio compression Input: External Audio in, Output: External Line out Support 2-way audio
Power over Ethernet	Yes
Video Output	Yes
Power Consumption	DC 12V Max: 4.2W, PoE Max: 802.3af, 5.3W
Operating Temperature	-20°C~50°C / -4°F~122°F
Dimensions	Sensor unit: 36.2x36.1, Main unit: 50x27x97.9 (mm)
Weight	380g
Network	
Ethernet	10/ 100 Base-T
Network Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, CoS, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google drive, Drop box, Onvif profile S
Wireless(Optional)	
Wireless	802.11b/ g/n
WPS	Yes
Security	WEP, WPA-PSK, WPA2-PSK
Power Consumption	DC 12V Max: 6.5W
Micro SD Card Management(Optional)	
Recording Trigger	Motion Detection, IP check, Network break down
Video Format	(wire only), Schedule, DI
Video Playback	AVI, JPEG
Delete Files	Yes
	Yes
Remote Browsing Requirement	
OS	Windows 10, Microsoft IE 11.0 or above
Hardware Suggested	Intel Dual Core 2.8G, RAM:4GB, Graphic card:128MB
Mobile Support	iOS 8 or above, Android 4.4.2 or above

System	
Video Resolution	1920x1080@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps
Video Adjust	Brightness, Contrast, Hue, Sharpness, Automatic Gain Control, Shutter Time, Sense-Up, D-WDR, Flip, Mirror, Day & Night Adjustable, Denoise
Triple Streaming	Yes
Image Snapshot	Yes
Full Screen Monitoring	Yes
Privacy Mask	Yes, 3 different areas
Compression Format	H.264+/ H.264/ M-JPEG
Video Bitrates Adjust	CBR, CVBR
Motion Detection	Yes, 3 Different Areas
Triggered Action	Mail, FTP, Save to SD card, SAMBA, DO
Pre/ Post Alarm	Yes, configurable
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely
Simultaneous Connection	Up to 10

◆ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

### Dimensions

