



4MP Box IP Camera

4MP, CS Mount, D-WDR

HLC-81KQ



- 4 Megapixel Box IP Camera
- H.264+/ H.264/ M-JPEG Compression
- Smart Stream / Video Output
- ROI Function / Quadruple Streaming
- Digital Noise Reduction
- Power over Ethernet
- Digital Wide Dynamic Range
- Day & Night Manual Switch Time Control
- IR Cut Filter Mechanism
- SD Card Backup
- Support iPhone/ Mac/ Android
- SDK for Software Integration
- Free Bundle 36 Ch Recording Software




Specification

| Hardware | |
|-----------------------------|---|
| CPU | Multimedia SoC |
| RAM | 512 MB |
| Flash | 32 MB |
| Image Sensor | 1 / 3" Megapixel CMOS Sensor |
| Lens | CS Mount |
| Sensitivity | Color: 0.08 Lux(AGC ON), B/W: 0.03 Lux(AGC ON) |
| Support DC IRIS | Yes |
| ICR | IR cut Filter Mechanism |
| I/O | 1 DI / 1 DO |
| Video Output | Yes |
| RS-485 | Yes |
| Audio | G.711(64K) and G.726(32K, 24K) audio compression Input: Microphone Built-in & Ø3.5 stereo jack (auto switch), Output: Ø3.5mm phone jack, Support 2-way |
| Power over Ethernet | Yes |
| Power Consumption | DC 12V: 2.7W, AC 24V Max: 5.3W, PoE Max: 3.6W |
| Wide Dynamic Range | 90 dB |
| S/N Ratio | 50 dB |
| Operating Temperature | -20°C~50°C / -4°F~122°F |
| Dimensions | W65 x H58 x L132 (mm) (without lens) |
| Weight | 450g (without lens) |
| Network | |
| Ethernet | 10/ 100 Base-T |
| Network Protocol | IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, CoS, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google drive, Drop box, Onvif profile S |
| Remote Browsing Requirement | |
| OS | Windows 10 Microsoft IE 11.0 or above |
| Hardware Suggested | Intel Dual Core 2.8G, RAM:4GB, Graphic card:128MB |
| Mobile Support | iOS 8 or above, Android 4.0.4 or above |

| System | |
|-------------------------------|--|
| Video Resolution | 2592x1520@25fps, 1920x1080@30fps, 1280x720@30fps, 640x360@30fps |
| Video Adjust | Brightness, Contrast, Hue, Saturation, Sharpness, Automatic Gain Control, Night Mode, Digital-WDR, Flip, Mirror, Noise Reduction, Lens Distortion Correction, Day & Night Adjustable |
| Features | ROI, Smart Stream, Motion Detection, Privacy Mask, Anti Fog, Tampering Detection, Corridor Mode, Push Video, BNC connector, P2P(Optional) |
| Quadruple Streaming | Yes |
| Image Snapshot | Yes |
| Full Screen Monitoring | Yes |
| Privacy Mask | Yes, 3 different areas |
| Compression Format | H.264+/ H.264/ M-JPEG |
| Video Bitrates Adjust | CBR, VBR |
| Motion Detection | Yes, 3 different areas |
| Triggered Action | Mail, FTP, Save to SD Card, DO, Samba, Dropbox, Google Drive |
| Pre/ Post Alarm | Yes, configurable |
| Security | Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP |
| Firmware Upgrade | HTTP mode, can be upgraded remotely |
| Simultaneous Connection | Up to 10 |
| Wireless (Optional) | |
| Wireless | 802.11b/ g/ n |
| Security | WEP, WPA-PSK, WPA2-PSK |
| Power Consumption | DC 12V: 3.7W, AC 24V Max: 6.3W |
| SD Card Management (Optional) | |
| Recording Trigger | Motion Detection, IP check, Network break down (wire only), Schedule, DI |
| Video Format | AVI, JPEG |
| Video Playback | Yes |
| Delete Files | Yes |

◆ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Dimensions



Accessories

| Product | 2.8-12mm F2.0, DC-Iris | 3-10.5mm F1.4, DC-Iris |
|---------|--|--|
| |  |  |

| | |
|-----------------|---|
| Product | Ø3.5mm Stereo Jack Microphone |
| Model | HTA-420 |
| Sensitivity | -38dB |
| Power | DC 12V |
| Frequency Range | 50 -10000Hz |
| Working Range | 5M |
| S/R ratio | 58dB |
| Impedance | Max 2.2K |
| Connector | 3.5mm female jack |
| Photo |  |

