



Fisheye Vandal Dome IP Camera

6.8MP, 1.1mm, 20M IR, T-WDR
IP68, IK10, Panoramic e-PTZ

HLV-1ZKS

- 6.8Megapixel SONY Starvis sensor
- H.264+/ H.264/ M-JPEG Compression
- Provides 360 Degrees Panorama View
- Advanced Smart Stream
- ROI Function
- DIS (Digital Image Stabilization)
- Digital Noise Reduction
- Hardware De-warp display mode
- Digital Wide Dynamic Range
- Day & Night Manual Switch Time Control
- Build-in IR 20M
- Power over Ethernet
- IR Cut Filter Mechanism
- Micro SD Card Backup
- 2-way Audio
- IP66, IP68
- IK10
- Support iPhone/iPad/Android
- SDK for Software Integration
- Free Bundle 36 Ch Recording Software



Specification

| Hardware | |
|----------------------------|---|
| CPU | Multimedia SoC |
| RAM | 512 MB |
| Flash | 128 MB |
| Image Sensor | 1/2.9" Sony Starvis CMOS Sensor |
| Lens Type | 1.1mm @ F2.0 |
| Sensitivity | Color: 0.1Lux (AGC ON) B/W: 0.05Lux (AGC ON) |
| View Angle | 360° |
| ICR | IR cut Filter Mechanism |
| I/O | 1 DI / 1 DO |
| Video Output | Yes |
| Audio | G.711 (64K) and G.726 (32K, 24K) audio compression, Input: 3.5mm phone jack, Output: 3.5mm phone jack, Support 2-way |
| Power over Ethernet | Yes |
| Power Consumption (IR On) | DC 12V Max: 5.72W, PoE Max: 6.84W |
| Operating Temperature | IR ON: 50°C, IR OFF: -20°C~60°C/ -4°F~140°F |
| Digital Wide Dynamic Range | 70 dB |
| S/N Ratio | 65 dB |
| Dimensions | Ø137 x H58 (mm) |
| Weight | 650 g |
| Casing | IK10, IP66, IP68 |
| IR LEDs | |
| LEDs | 4 Units High Power |
| IR Distance | 20 M |

| System | |
|-------------------------|--|
| Video Resolution | 2880x2160@25fps, 1920x1080@30fps, 1280x720@30fps, 640x480@30fps |
| Video Adjust | Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Night Mode, WDR, Flip, Mirror, Noise Reduction, Day & Night Adjustable |
| Features | ROI, Smart Stream, Advanced Smart Stream, Motion Detection, Privacy Mask, Anti Fog, Tampering Detection, Corridor Mode, Push Video, P2P(Optional) |
| Quadruple Streaming | Yes |
| De-warping mode | 1O/ 1P1R/ 2P/ 1P2R/ 1P3P/ 1O3R |
| Mount Type | Ceiling/ Wall/ Desk |
| e-PTZ | Yes |
| Image Snapshot | Yes |
| Full Screen Monitoring | Yes |
| Privacy Mask | Yes, 3 different areas |
| Compression Format | H.264+/ H.264/ M-JPEG |
| Video Bitrates Adjust | CBR, VBR |
| Motion Detection | Yes, 3 different areas |
| Triggered Action | Mail, FTP, Save to SD card, DO, Samba, Dropbox, Google Drive |
| Pre/ Post Alarm | Yes, configurable |
| Security | Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP |
| Firmware Upgrade | HTTP mode, can be upgraded remotely |
| Simultaneous Connection | Up to 10 |


Specification

| Network | |
|------------------|---|
| Ethernet | 10/ 100 Base-T |
| Network Protocol | IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, CoS, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google drive, Drop box, Onvif profile S |

| IR LEDs | |
|--------------------------|---|
| Recording Trigger | Motion Detection, IP check, Network break down(wire only), Schedule, DI |
| Video Format | AVI, JPEG |
| Video Playback | Yes |
| Delete Files | Yes |
| Web Browsing Requirement | |
| Hardware Suggested | Windows 7, 8, 10, XP, Microsoft IE 6.0 or above |
| OS | iOS 8 or above, Android 4.4.2 or above |
| Mobile Support | Intel Dual Core: 2.8G, RAM: 4GB, Graphic card: 128MB |

◆SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Dimensions



Accessories

| | |
|------------|---|
| Product | L-shape Bracket |
| Model | aHTB-F01000010, aHTB-F01000011 |
| Material | Aluminum Alloy |
| Dimensions | 140 x 215 x 106 mm |
| Photo |  |

| | |
|----------------------------|---|
| Product | Pole Mount Adapter |
| Model | aHTB-F01000002 |
| Material | Aluminum Alloy, SPCC FEVE |
| Dimensions | 156 x 150 x 63 mm |
| Suitable for Pole Diameter | 102 - 152mm (4-6 inch) |
| Photo |  |

| | |
|-----------------|---|
| Product | Ø3.5mm Stereo Jack Microphone |
| Model | HTA-420 |
| Sensitivity | -38dB |
| Power | DC 12V |
| Frequency Range | 50 - 10000Hz |
| Working Range | 5M |
| S/R ratio | 58dB |
| Impedance | Max 2.2K |
| Connector | 3.5mm female jack |
| Photo |  |

