



8MP Bullet IP Camera

8MP, 3.6X Zoom, 40M IR
T-WDR, IP68, IK10

HLZ-7BKU(3.6X)

- 8 Megapixel IR Bullet IP Camera
- H.264+/ H.264/ M-JPEG Compression
- Advanced Smart Stream
- ROI Function
- Smart Focus System for Remote Focus Adjustment
- Digital Noise Reduction
- Power over Ethernet
- True Wide Dynamic Range 120dB
- Day & Night Manual Switch Time Control
- IR LED Built-in 40M
- IR Cut Filter Mechanism
- Micro SD Card Backup
- 2-way Audio
- IP66, IP68, IK10
- Cable Management
- Support iPhone/ Android/ Mac
- SDK for Software Integration
- Free Bundle 36 Ch Recording Software



Specification

Hardware	
CPU	Multimedia SoC
RAM	1GB
Flash	128MB
Image Sensor	1/2.5" Sony Starvis CMOS Sensor
Sensitivity	Color: 0.01 Lux(AGC ON), B/W: 0.005 Lux(AGC ON)
Lens Type	3.3-12mm 3.6X Bulid-in Zoom Lens @ F1.4
View Angle	38°~103°(H), 21°~55°(V)
ICR	IR cut Filter Mechanism
I/O	1 DI/ 1 DO
Power over Ethernet	Yes
Video Output	Yes
Audio	G.711(64K) and G.726(32K, 24K) audio compression, Input: Ø3.5mm phone jack, Output: Ø3.5mm phone jack, Support 2-way.
Power Consumption	DC 12V Max: 7.5W, PoE Max: 8.5W
Operating Temperature	IR ON: 50°C, IR OFF: -20°C~60°C / -4°F~140°F
Wide Dynamic Range	120dB
S/N Ratio	60dB
Dimensions	Ø77.4 x H122.5 (mm)
Weight	720g
Network	
Ethernet	10/ 100 Base-T
Network Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, CoS, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google drive, Drop box, Onvif profile S

System	
Video Resolution [16:9]	3840x2160@30fps, 2592x1520@30fps, 1920x1080@30fps, 1280x720@30fps, 640x360@30fps
Video Adjust	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Night Mode, WDR, Flip, Mirror, Noise Reduction, Day&Night Adjustable, LDC, ROI, Smart
Features	Stream, Advanced Smart Stream, Motion Detection, Privacy Mask, Anti Fog, Tampering, Detection, Corridor Mode, Push Video, P2P (Optional)
Quadruple Streaming	Yes
Image Snapshot	Yes
Full Screen Monitoring	Yes
Privacy Mask	Yes, 3 different areas
Compression Format	H.264+/ H.264/ M-JPEG
Video Bitrates Adjust	CBR, VBR
Motion Detection	Yes, 3 different areas
Triggered Action	Mail, FTP, Save to SD card, DO, Samba, Google Drive, Dropbox
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely
Simultaneous Connection	Up to 10
Wireless (Optional)	
Wireless	802.11b/g/n
Security	WEP, WPA-PSK, WPA2-PSK
Power Consumption	DC 12V Max: 8.5 W


Specification

IR LEDs	
LEDs	5 x High Power LEDs, 850nm
IR Distance	40M
Remote Browsing Requirement	
OS	Windows 10 Microsoft IE 11.0 or above
Hardware Suggested	Intel Core i7-4790 4GHz, 8G DDR, NV GeForce GTX750
Mobile Support	iOS 8 or above, Android 4.4.2 or above.

Micro SD Card Management (Optional)	
Recording Trigger	Motion Detection, IP check, Network break down (wire only), Schedule, DI
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes

◆ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Dimensions



Accessories

Product	Pole Mount Adapter	Junction Box
Model	aHTB-F01000001	aHTB-E01
Material	Aluminum Alloy, SPCC FEVE	SUS 316L
Dimensions	156 x 150 x 63 mm	Ø137x H58.7 mm
Suitable for Pole Diameter	102 - 152mm (4-6 inch)	
Photo		

Product	Ø3.5mm Stereo Jack Microphone
Model	HTA-420
Sensitivity	-38dB
Power	DC 12V
Frequency Range	50 -10000Hz
Working Range	5M
S/R ratio	58dB
Impedance	Max 2.2K
Connector	3.5mm female jack
Photo	

