


Product Datasheet

8-port 10/100M PoE Injector

ONV-PSE3108



OVERVIEW

PoE Injector is also called as power over Ethernet mid-span devices. 8-port PoE injector, that is PoE power supply module, is the most flexible and the hottest products among the power supply devices. There are 8x RJ45 PoE ports for these 8-port PoE injector. This mid-span have 8*2 RJ45 network ports, one group of network ports will use for upper Ethernet switches or other network devices, another group of network ports will support POE power supply output with network data output.

These 8-port PoE injectors provide a simple, economical, high-performance and intelligent way for Ethernet PoE power supply and data communication. It's an ideal choice for those who need a superior quality project because of its simple use, easy to install, superior performance and cost-effective. They can supply power to HD webcam through Cat5 Ethernet cable, in order that makes it more flexible for the places difficult to connect to the power supply and provide more efficient solutions.

FEATURE


- ◇ Supply power to HD network surveillance cameras with Cat5e (PoE)
- ◇ 16*10/100M RJ45 ports, 8*10/100M PoE ports
- ◇ AC input 100V~240V 50-60Hz.
- ◇ Compatible with IEEE802.3af/at standard
- ◇ Coming with the Ethernet network port and PoE output port, and the power input port with lighting-proof function (meet the secondary lightning protection)
- ◇ Can supply power with the spare line pair(4/5 (+), 7/8 (-) method or the data line pair 1/2(+), 3/6(-) method
- ◇ No fan, natural heat dissipation, small, quiet design, suitable for desktop or wall

TECHNICAL SPECIFICATION

Model	ONV-PSE3108	ONV-PSE3108-at
Port Description	1x AC input port 8*10/100M PoE ports 16*10/100M RJ45 ports	
Power Supply Pin	mid-span: 4/5, 7/8 data line pair(default); end-span: 1/2,3/6 spare line pair (can be customized)	
Network Medium	100BASE-TX: 5Cat and more UTP (≤100 meters)	
Thermal Protection	>100°C	
Working Rate	10/100Mbps	
Network Port Protection	IEC61000-4-2(ESD)	
MTBF	100,000 hours	
LEDs Indicator	PoE working status	


PoE Standards	IEEE802.3af/at	
Total Power	130W	250W
Max Power Per Port	30W, IEEE802.3af/at	
AC Input Voltage	100~240V, 50~60Hz 0.5A	
Dimensions	280x186x44mm	
Weight	1.49kg	1.565kg
Operation TEMP / Humidity	-20°~55°C;10%~90%% RH Non condensing	
Storage TEMP / Humidity	-20°~75°C;10%~95% RH Non condensing	
Certification	CE mark,commercial,FCC Part 15 Class B, RoHS	
Warranty	3 years	

DIMENSION



- A. RJ45 PoE Output
- B. Ethernet RJ45 Input
- C. PoE Status Light
- D. AC 220V/50Hz Input

APPLICATION



ORDERING INFORMATION

Model	Description
ONV-PSE3108	10/100M PoE injector with 16*10/100M RJ45 ports. 8*10/100M PoE ports, IEEE802.3af/at. Total power up to 130W.
ONV-PSE3108-at	10/100M PoE injector with 16*10/100M RJ45 ports. 8*10/100M PoE ports, IEEE802.3af/at. Total power up to 250W.
ONV-PSE3308	Gigabit PoE injector with 16*10/100/1000M RJ45 ports. 8*10/100/1000M PoE ports, IEEE802.3af/at. Total power up to 130W.
ONV-PSE3308-at	Gigabit PoE injector with 16*10/100/1000M RJ45 ports. 8*10/100/1000M PoE ports, IEEE802.3af/at. Total power up to 250W.

Notes: Default mid-span: 4/5, 7/8 data line pair; end-span: 1/2, 3/6 spare line pair (can be customized)

PACKING LIST

PACKING LIST	CONTENT	QTY	UNIT
	8-port 10/100M PoE injector	1	SET
	Power Cable	1	PC
	User Guide	1	PC
	Warranty Card	1	PC

CONTACT US



OPTICAL NETWORK VIDEO TECHNOLOGIES (SHENZHEN) CO., LTD

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Website: www.onvcom.com

Zip: 518000

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen, China

Factory Address: The 4-6th Floor, No. 59, Huaning Road, Xinwei Community, Dalang Street,

Longhua District, Shenzhen, China

