



## LAN-10G2T-X550

|                                 |  |
|---------------------------------|--|
| Controller                      | Intel Ethernet Controller X550   |
| Number of Ports                 | 2 x BASE-T (RJ45)  |
| Connector                       | Base-T (RJ45)  |
| PCIe and Lanes                  | PCIe Gen3 x4   |
| Transmission Rates              | 10Gbps   |
| Bracket                         | full-height and specialized for QNAP NAS   |
| SR-IOV Support                  | Yes  |
| Supported NAS operating systems | QTS/QuTS hero (recommend an upgrade to the latest version); Windows 10 (1809 or later); Linux Stable Kernel 4.20/5.x; Windows Server 2019 ( <u>Driver required</u> ) |
| Supported QNAP NAS              | Models with PCIe slot(s) (1 free slot required)  |
| Port and Cable                  | RJ-45; over CAT-6 class cable  |
| Package Content                 | 1 x Network card (Low-profile bracket pre-installed); 1 x QIG; 2 x Brackets (full-height and specialized for QNAP NAS); 1 x Cable (CAT 6a, 1.8m)                     |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.